

Description


thread: 1/4-28, drilled, thin, NAS1423 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS14234
Minimum Qty (MOQ):	10
NSN:	5310-00-962-5166
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1423-4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Nut Style:	Hexagon
Nut Height:	0.115 Inches Minimum And 0.135 Inches Maximum
Drilled Hole Diameter:	0.046 Inches Nominal
Hole Type And Quantity:	3 Drilled
Width Across Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Thread Series:	Unf
Thread Quantity Per Inch:	28
Hardness Rating:	34.0 Rockwell C Minimum And 38.0 Rockwell C Maximum
Nominal Thread Size:	0.250 Inches
Hole Configuration Style:	Configuration B
Countersink Angle:	110.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	250.0 Microinches
Material:	Steel Comp 4130 Overall Or Steel Comp E4340 Overall Or Steel Comp 4340 Overall
Material Document And Classification:	MI-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this plain hexagon nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS1423-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.