

Description

thread: 1/4-28, drilled, thin, NAS1423 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS14234 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-00-962-5166 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1423-4 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Nut Style: | Hexagon |
| Nut Height: | 0.115 Inches Minimum And 0.135 Inches Maximum |
| Drilled Hole Diameter: | 0.046 Inches Nominal |
| Hole Type And Quantity: | 3 Drilled |
| Width Across Flats: | 0.428 Inches Minimum And 0.440 Inches Maximum |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 28 |
| Hardness Rating: | 34.0 Rockwell C Minimum And 38.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.250 Inches |
| Hole Configuration Style: | Configuration B |
| Countersink Angle: | 110.0 Degrees Nominal Nut |
| Bearing Surface Type: | Chamfered Or Washer Faced |
| Bearing Surface Finish: | 250.0 Microinches |
| Material: | Steel Comp 4130 Overall Or Steel Comp E4340 Overall Or Steel Comp 4340 Overall |
| Material Document And Classification: | MI-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this plain hexagon nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS1423-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.