

P/N NAS1423-7LH

Description

Thread Size: 1/2", Nut Height: 1/8", Head Width: 5/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS14237LH

Minimum Qty (MOQ): 10 EA

NSN: 5310-00-959-1851

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1423-7LH Specifications

| Thread Class: | 3b |
|--|--|
| Thread Direction: | Left-hand |
| Nut Style: | Hexagon |
| Nut Height: | 0.146 Inches Minimum And 0.166 Inches Maximum |
| Drilled Hole Diameter: | 0.046 Inches Nominal |
| Hole Type And Quantity: | 3 Drilled |
| Width Across Flats: | 0.615 Inches Minimum And 0.627 Inches Maximum |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 20 |
| Hardness Rating: | 34.0 Rockwell C Minimum And 38.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.438 Inches |
| Hole Configuration Style: | Configuration B |
| Countersink Angle: | 110.0 Degrees Nominal Nut |
| Bearing Surface Type: | Chamfered Or Washer Faced |
| Bearing Surface Finish: | 250.0 Microinches |
| Material: | Steel Comp 4130 Overall Or Steel Comp E4340 Overall |
| Material Document And Classification: | Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this nut from our inventory online by visiting https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS1423-7LH and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.