

**Description**

Thread Size: 1/8", Nut Height: 1/8", Head Width: 1/4", three holes, NAS1423 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1423C06                                |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5310-01-127-7105                          |
| Schedule B:             | 7318.16.0000                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1423C06 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3b   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Nut Style:</b>                                     | Hexagon  |
| <b>Nut Height:</b>                                    | 0.100 Inches Nominal   |
| <b>Drilled Hole Diameter:</b>                         | 0.034 Inches Minimum And 0.039 Inches Maximum  |
| <b>Hole Type And Quantity:</b>                        | 3 Drilled  |
| <b>Width Across Flats:</b>                            | 0.303 Inches Minimum And 0.315 Inches Maximum  |
| <b>Thread Series:</b>                                 | Unjc   |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Nominal Thread Size:</b>                           | 0.138 Inches   |
| <b>Hole Configuration Style:</b>                      | Configuration B  |
| <b>Countersink Angle:</b>                             | 110.0 Degrees Nominal Nut  |
| <b>Bearing Surface Type:</b>                          | Chamfered  |
| <b>Bearing Surface Finish:</b>                        | 125.0 Microinches  |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall   |
| <b>Specification/standard Data:</b>                   | 80205-nas1423 Professional/industrial Association Specification  |

## How to Order

Order this plain hexagon nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS1423C06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.