

Description

Thread Size: 5/8", Nut Height: 1/4", Head Width: 1"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1423C10LH
Minimum Qty (MOQ):	5 EA
NSN:	5310-01-151-6102
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1423C10LH Specifications

Thread Class:	3b
Thread Direction:	Left-hand
Nut Style:	Hexagon
Nut Height:	0.193 Inches Minimum And 0.213 Inches Maximum
Drilled Hole Diameter:	0.045 Inches Minimum And 0.050 Inches Maximum
Hole Type And Quantity:	3 Drilled
Width Across Flats:	0.986 Inches Minimum And 1.002 Inches Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	18
Nominal Thread Size:	0.625 Inches
Hole Configuration Style:	Configuration B
Countersink Angle:	110.0 Degrees Nominal Both Ends
Bearing Surface Type:	Chamfered
Bearing Surface Finish:	125.0 Microinches
Special Features:	150000 Psi Min Tensile Strength
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1423 Professional/industrial Association Standard

How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/misc+nuts/NAS1423C10LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.