

Description

Thread Size: 1-3/4", Nut Height: 3/8", Head Width: 2-1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1423C28 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5310-01-233-0590 |
| Schedule B: | 7318.16.0085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1423C28 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Nut Style: | Hexagon |
| Nut Height: | 0.358 Inches Nominal |
| Drilled Hole Diameter: | 0.069 Inches Minimum And 0.074 Inches Maximum |
| Hole Type And Quantity: | 3 Drilled |
| Width Across Flats: | 2.222 Inches Minimum And 2.252 Inches Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 12 |
| Nominal Thread Size: | 1.750 Inches |
| Hole Configuration Style: | Configuration B |
| Countersink Angle: | 110.0 Degrees Nominal Both Ends |
| Bearing Surface Type: | Chamfered |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1423 Professional/industrial Association Standard |

How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/misc+nuts/NAS1423C28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.