

Description

Thread Size: 1/4", Nut Height: 1/8", Head Width: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1423C5LH |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5310-01-141-2511 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1423C5LH Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Left-hand |
| Nut Style: | Hexagon |
| Nut Height: | 0.125 Inches Nominal |
| Drilled Hole Diameter: | 0.045 Inches Minimum And 0.050 Inches Maximum |
| Hole Type And Quantity: | 3 Drilled |
| Width Across Flats: | 0.490 Inches Minimum And 0.502 Inches Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 24 |
| Nominal Thread Size: | 0.312 Inches |
| Hole Configuration Style: | Configuration B |
| Bearing Surface Type: | Chamfered |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1423 Professional/industrial Association Standard |

How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/misc+nuts/NAS1423C5LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.