

Description

Thread Size: 7/16", Nut Height: 5/32", Head Width: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1423C7LH
Minimum Qty (MOQ):	5
NSN:	5310-01-198-3483
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1423C7LH Specifications

Thread Class:	3b
Thread Direction:	Left-hand
Nut Style:	Hexagon
Nut Height:	0.146 Inches Minimum And 0.166 Inches Maximum
Drilled Hole Diameter:	0.045 Inches Minimum And 0.050 Inches Maximum
Hole Type And Quantity:	3 Drilled
Width Across Flats:	0.615 Inches Minimum And 0.627 Inches Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	20
Nominal Thread Size:	0.4375 Inches
Hole Configuration Style:	Configuration B
Countersink Angle:	109.0 Degrees Minimum Both Ends And 111.0 Degrees Maximum Both Ends
Bearing Surface Type:	Chamfered
Bearing Surface Finish:	125.0 Microinches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1423 Professional/industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1423C7LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.