

**Description**

Thread Size: 7/16", Nut Height: 5/32", Head Width: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1423C7LH
Minimum Qty (MOQ):	5
NSN:	5310-01-198-3483
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1423C7LH Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Left-hand
<b>Nut Style:</b>	Hexagon
<b>Nut Height:</b>	0.146 Inches Minimum And 0.166 Inches Maximum
<b>Drilled Hole Diameter:</b>	0.045 Inches Minimum And 0.050 Inches Maximum
<b>Hole Type And Quantity:</b>	3 Drilled
<b>Width Across Flats:</b>	0.615 Inches Minimum And 0.627 Inches Maximum
<b>Thread Series:</b>	Unjf
<b>Thread Quantity Per Inch:</b>	20
<b>Nominal Thread Size:</b>	0.4375 Inches
<b>Hole Configuration Style:</b>	Configuration B
<b>Countersink Angle:</b>	109.0 Degrees Minimum Both Ends And 111.0 Degrees Maximum Both Ends
<b>Bearing Surface Type:</b>	Chamfered
<b>Bearing Surface Finish:</b>	125.0 Microinches
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5525 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1423 Professional/Industrial Association Standard

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1423C7LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.