

Description

Thread Size: 1/2", Nut Height: 1/8", Head Width: 3/4", drilled

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1423C8 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5310-01-058-4656 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1423C8 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Nut Style: | Hexagon |
| Nut Height: | 0.146 Inches Minimum And 0.166 Inches Maximum |
| Drilled Hole Diameter: | 0.045 Inches Minimum And 0.050 Inches Maximum |
| Hole Type And Quantity: | 3 Drilled |
| Width Across Flats: | 0.740 Inches Minimum And 0.752 Inches Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 20 |
| Nominal Thread Size: | 0.500 Inches |
| Hole Configuration Style: | Configuration B |
| Countersink Angle: | 109.0 Degrees Minimum Nut And 111.0 Degrees Maximum Nut |
| Bearing Surface Type: | Chamfered |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Iron Alloy 660 Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1423 Professional/Industrial Association Standard |

How to Order

Order this misc nut from our inventory online by visiting <https://military-fasteners.com/nuts/misc+nuts/NAS1423C8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.