

Description

Thread Size: 1/2", Nut Height: 1/8", Head Width: 3/4", drilled

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1423C8
Minimum Qty (MOQ):	5
NSN:	5310-01-058-4656
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1423C8 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Nut Style:	Hexagon
Nut Height:	0.146 Inches Minimum And 0.166 Inches Maximum
Drilled Hole Diameter:	0.045 Inches Minimum And 0.050 Inches Maximum
Hole Type And Quantity:	3 Drilled
Width Across Flats:	0.740 Inches Minimum And 0.752 Inches Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	20
Nominal Thread Size:	0.500 Inches
Hole Configuration Style:	Configuration B
Countersink Angle:	109.0 Degrees Minimum Nut And 111.0 Degrees Maximum Nut
Bearing Surface Type:	Chamfered
Bearing Surface Finish:	125.0 Microinches
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1423 Professional/Industrial Association Standard

How to Order

Order this misc nut from our inventory online by visiting <https://military-fasteners.com/nuts/misc+nuts/NAS1423C8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.