

## **P/N NAS1423C9**

## **Description**

Thread Size: 1/2", Nut Height: 1/4", Head Width: 7/8", drilled

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1423C9

Minimum Qty (MOQ):

NSN: 5310-01-122-5482

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







# **P/N NAS1423C9 Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Nut Style:	Hexagon
Nut Height:	0.193 Inches Minimum And 0.213 Inches Maximum
Drilled Hole Diameter:	0.083 Inches Minimum And 0.103 Inches Maximum
Hole Type And Quantity:	3 Drilled
Width Across Flats:	0.863 Inches Minimum And 0.877 Inches Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	18
Nominal Thread Size:	0.562 Inches
Hole Configuration Style:	Configuration B
Countersink Angle:	109.0 Degrees Minimum Both Ends And 111.0 Degrees Maximum Both Ends
Bearing Surface Type:	Chamfered
Bearing Surface Finish:	125.0 Microinches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1423 Professional/industrial Association Standard

## **How to Order**

Order this plain hexagon nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS1423C9">https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS1423C9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.