

Description

Fastener Length: 17/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS142402 |
| Minimum Qty (MOQ): | 35 |
| NSN: | 5320-00-923-1695 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N NAS1424-02 Specifications

| | |
|---|---|
| Fastener Length: | 0.258 Inches Minimum And 0.268 Inches Maximum |
| Head Style: | Straight Pan |
| Head Height: | 0.028 Inches Minimum And 0.040 Inches Maximum |
| Shank Diameter: | 0.124 Inches Minimum And 0.125 Inches Maximum |
| Shank Style: | Stump |
| Head Major Diameter: | 0.181 Inches Minimum And 0.195 Inches Maximum |
| Grip Length: | 0.063 Inches Minimum And 0.125 Inches Maximum |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1424-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.