

Description

Fastener Length: 29/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS142404
Minimum Qty (MOQ):	15
NSN:	5320-00-150-4221
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1424-04 Specifications

Fastener Length:	0.443 Inches Minimum And 0.453 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.028 Inches Minimum And 0.040 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.125 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.181 Inches Minimum And 0.195 Inches Maximum
Grip Length:	0.189 Inches Minimum And 0.250 Inches Maximum
Features Provided:	Casehardened
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	76.1 Rockwell Superficial 15-n Minimum Overall And 80.9 Rockwell Superficial 15-n Maximum Overall
Shear Strength:	1150 Single Pounds Per Square Inch
Special Features:	Rockwell Cscale 37 Min 41 Max Core Hardness
Material:	Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Qq-w-405 Fed Spec All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1424 Professional/industrial Association Standard

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1424-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.