

Description

Fastener Length: 29/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | NAS142404 |
| Minimum Qty (MOQ): | 15 |
| NSN: | 5320-00-150-4221 |
| Schedule B: | 7318.24.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N NAS1424-04 Specifications

| | |
|---|---|
| Fastener Length: | 0.443 Inches Minimum And 0.453 Inches Maximum |
| Head Style: | Straight Pan |
| Head Height: | 0.028 Inches Minimum And 0.040 Inches Maximum |
| Shank Diameter: | 0.124 Inches Minimum And 0.125 Inches Maximum |
| Shank Style: | Stump |
| Head Major Diameter: | 0.181 Inches Minimum And 0.195 Inches Maximum |
| Grip Length: | 0.189 Inches Minimum And 0.250 Inches Maximum |
| Features Provided: | Casehardened |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 76.1 Rockwell Superficial 15-n Minimum Overall And 80.9 Rockwell Superficial 15-n Maximum Overall |
| Shear Strength: | 1150 Single Pounds Per Square Inch |
| Special Features: | Rockwell Cscale 37 Min 41 Max Core Hardness |
| Material: | Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Qq-w-405 Fed Spec All Material Responses Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1424 Professional/industrial Association Standard |

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1424-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.