

**Description**

Fastener Length: 29/64

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS142404
Minimum Qty (MOQ):	15
NSN:	5320-00-150-4221
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1424-04 Specifications

<b>Fastener Length:</b>	0.443 Inches Minimum And 0.453 Inches Maximum
<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.028 Inches Minimum And 0.040 Inches Maximum
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.125 Inches Maximum
<b>Shank Style:</b>	Stump
<b>Head Major Diameter:</b>	0.181 Inches Minimum And 0.195 Inches Maximum
<b>Grip Length:</b>	0.189 Inches Minimum And 0.250 Inches Maximum
<b>Features Provided:</b>	Casehardened
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	76.1 Rockwell Superficial 15-n Minimum Overall And 80.9 Rockwell Superficial 15-n Maximum Overall
<b>Shear Strength:</b>	1150 Single Pounds Per Square Inch
<b>Special Features:</b>	Rockwell Cscale 37 Min 41 Max Core Hardness
<b>Material:</b>	Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Qq-w-405 Fed Spec All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1424 Professional/industrial Association Standard

## How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1424-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.