

Description

Pin part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1424H03
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-058-4115
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	096300, Rivets Brass / Bronze / Copper

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1424H03 Specifications

Head Style:	Straight Pan
Head Height:	0.028 Inches Minimum And 0.040 Inches Maximum
Shank Diameter:	0.1235 Inches Minimum And 0.1250 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.181 Inches Minimum And 0.195 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.126 Inches Minimum And 0.188 Inches Maximum
Features Provided:	Sealant Vent Groove
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	77.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
Material:	Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Astm A547 Assn Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1424 Professional/industrial Association Standard

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1424H03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.