

**Description**

Pin part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1424H03
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-058-4115
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	096300, Rivets Brass / Bronze / Copper

NO IMAGE  
AVAILABLE

## P/N NAS1424H03 Specifications

<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.028 Inches Minimum And 0.040 Inches Maximum
<b>Shank Diameter:</b>	0.1235 Inches Minimum And 0.1250 Inches Maximum
<b>Shank Style:</b>	Stump
<b>Head Major Diameter:</b>	0.181 Inches Minimum And 0.195 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.126 Inches Minimum And 0.188 Inches Maximum
<b>Features Provided:</b>	Sealant Vent Groove
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	77.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
<b>Material:</b>	Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	Astm A547 Assn Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1424 Professional/industrial Association Standard

## How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1424H03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.