

Description

Fastener Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1425H03
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-426-3151
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1425H03 Specifications

Fastener Length:	0.356 Inches Minimum And 0.366 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.036 Inches Minimum And 0.048 Inches Maximum
Shank Diameter:	0.1550 Inches Minimum And 0.1565 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.235 Inches Minimum And 0.249 Inches Maximum
Grip Length:	0.126 Inches Minimum And 0.188 Inches Maximum
Material:	Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Astm A547 Assn Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1425H03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.