

Description

Fastener Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1425H03
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-426-3151
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N NAS1425H03 Specifications

<b>Fastener Length:</b>	0.356 Inches Minimum And 0.366 Inches Maximum
<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.036 Inches Minimum And 0.048 Inches Maximum
<b>Shank Diameter:</b>	0.1550 Inches Minimum And 0.1565 Inches Maximum
<b>Shank Style:</b>	Stump
<b>Head Major Diameter:</b>	0.235 Inches Minimum And 0.249 Inches Maximum
<b>Grip Length:</b>	0.126 Inches Minimum And 0.188 Inches Maximum
<b>Material:</b>	Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	Astm A547 Assn Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall

## How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1425H03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.