

### **Description**

Fastener Length: 37/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

### **Additional Information**

SKU / Model:	NAS1426H06
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-381-9608
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N NAS1426H06 Specifications

<b>Fastener Length:</b>	0.569 Inches Minimum And 0.579 Inches Maximum
<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.044 Inches Minimum And 0.056 Inches Maximum
<b>Shank Diameter:</b>	0.1880 Inches Minimum And 0.1895 Inches Maximum
<b>Shank Style:</b>	Grooved
<b>Head Major Diameter:</b>	0.288 Inches Minimum And 0.302 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.313 Inches Minimum And 0.375 Inches Maximum
<b>Features Provided:</b>	Sealant Vent Groove
<b>Minimum Tensile Strength:</b>	1410 Pounds Per Square Inch
<b>Shear Strength:</b>	5380 Double Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Astm A547 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1426 Professional/industrial Association Standard

## How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1426H06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.