

Description

Fastener Length: 37/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1426H06
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-381-9608
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1426H06 Specifications

Fastener Length:	0.569 Inches Minimum And 0.579 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.044 Inches Minimum And 0.056 Inches Maximum
Shank Diameter:	0.1880 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Grooved
Head Major Diameter:	0.288 Inches Minimum And 0.302 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Features Provided:	Sealant Vent Groove
Minimum Tensile Strength:	1410 Pounds Per Square Inch
Shear Strength:	5380 Double Pounds Per Square Inch
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Astm A547 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1426 Professional/industrial Association Standard

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1426H06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.