

Description

NAS1436-16 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS143616 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-00-558-6341 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N NAS1436-16 Specifications

| | |
|---|---|
| Fastener Length: | 3.120 Inches Minimum And 3.320 Inches Maximum |
| Head Style: | Flush Countersunk |
| Shank Diameter: | 0.188 Inches Minimum And 0.190 Inches Maximum |
| Shank Style: | Pin-rivet, Multiple Grooved |
| Head Major Diameter: | 0.262 Inches Minimum |
| Grip Length: | 0.939 Inches Minimum And 1.000 Inches Maximum |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/NAS1436-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.