

**Description**

NAS1436-16 Pin-Rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS143616
Minimum Qty (MOQ):	10
NSN:	5320-00-558-6341
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1436-16 Specifications

<b>Fastener Length:</b>	3.120 Inches Minimum And 3.320 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Shank Diameter:</b>	0.188 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.262 Inches Minimum
<b>Grip Length:</b>	0.939 Inches Minimum And 1.000 Inches Maximum
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/NAS1436-16](https://military-fasteners.com/pins/pin_rivets/NAS1436-16) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.