

Description

Fastener Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1436H02
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-343-5396
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1436H02 Specifications

Fastener Length:	0.314 Inches Minimum And 0.324 Inches Maximum
Head Style:	Flush Countersunk
Shank Diameter:	0.1880 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.263 Inches Minimum And 0.305 Inches Maximum
Grip Length:	0.062 Inches Minimum And 0.125 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Sealant Escape Groove
Material:	Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Astm A547 Assn Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1436 Professional/industrial Association Standard

How to Order

Order this swage locking pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1436H02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.