

**Description**

Fastener Length: 1-13/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1436H04
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-400-4062
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N NAS1436H04 Specifications

<b>Fastener Length:</b>	1.620 Inches Minimum And 1.820 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Shank Diameter:</b>	0.188 Inches Minimum And 0.189 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.305 Inches Maximum
<b>Grip Length:</b>	0.189 Inches Minimum And 0.250 Inches Maximum
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Heat Treatment:</b>	As Fabricated Overall
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Ams 6300 Assn Std Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Stp 58-001,type 2,class 2,lockheed-georgia Co Mfr Ref Single Treatment Response Overall

## How to Order

Order this swage locking pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1436H04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.