

Description

Fastener Length: 1-13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | NAS1436H04 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-00-400-4062 |
| Schedule B: | 7318.24.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N NAS1436H04 Specifications

| | |
|---|--|
| Fastener Length: | 1.620 Inches Minimum And 1.820 Inches Maximum |
| Head Style: | Flush Countersunk |
| Shank Diameter: | 0.188 Inches Minimum And 0.189 Inches Maximum |
| Shank Style: | Pin-rivet, Multiple Grooved |
| Head Major Diameter: | 0.305 Inches Maximum |
| Grip Length: | 0.189 Inches Minimum And 0.250 Inches Maximum |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Heat Treatment: | As Fabricated Overall |
| Material: | Steel Overall |
| Material Document And Classification: | Ams 6300 Assn Std Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Stp 58-001,type 2,class 2,lockheed-georgia Co Mfr Ref Single Treatment Response Overall |

How to Order

Order this swage locking pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1436H04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.