

Description

Fastener Length: 1-63/64", NAS1436 series pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1436H06 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5320-00-400-4063 |
| Schedule B: | 7318.24.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N NAS1436H06 Specifications

| | |
|--|--|
| Fastener Length: | 1.880 Inches Minimum And 2.080 Inches Maximum |
| Head Style: | Flush Countersunk |
| Shank Diameter: | 0.188 Inches Minimum And 0.189 Inches Maximum |
| Shank Style: | Pin-rivet, Multiple Grooved |
| Head Major Diameter: | 0.305 Inches Maximum |
| Grip Length: | 0.313 Inches Minimum And 0.375 Inches Maximum |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Heat Treatment: | As Fabricated Overall |
| Material: | Steel Overall |
| Material Document And Classification: | Ams 6300 Assn Std Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/NAS1436H06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.