



★ FASTENERS

Military-Fasteners.com

P/N NAS1436H06

Description

Fastener Length: 1-63/64", NAS1436 series pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1436H06
Minimum Qty (MOQ):	20
NSN:	5320-00-400-4063
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1436H06 Specifications

Fastener Length:	1.880 Inches Minimum And 2.080 Inches Maximum
Head Style:	Flush Countersunk
Shank Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.305 Inches Maximum
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Heat Treatment:	As Fabricated Overall
Material:	Steel Overall
Material Document And Classification:	Ams 6300 Assn Std Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/NAS1436H06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.