

**Description**

Swage Locking Pin part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1436H10
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-236-0539
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

## P/N NAS1436H10 Specifications

<b>Head Style:</b>	Flush Countersunk
<b>Shank Diameter:</b>	0.1880 Inches Minimum And 0.1895 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.305 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.563 Inches Minimum And 0.625 Inches Maximum
<b>Features Provided:</b>	Sealant Vent Groove
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	77.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	Astm A547 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this swage locking pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1436H10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.