

Description

NAS1438-15 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS143815
Minimum Qty (MOQ):	10
NSN:	5320-00-558-3790
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1438-15 Specifications

Fastener Length:	3.160 Inches Minimum And 3.360 Inches Maximum
Head Style:	Flush Countersunk
Shank Diameter:	0.248 Inches Minimum And 0.250 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.344 Inches Minimum
Grip Length:	0.876 Inches Minimum And 0.938 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/NAS1438-15 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.