

Description

NAS1438-15 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS143815 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-00-558-3790 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



NO IMAGE
AVAILABLE

P/N NAS1438-15 Specifications

| | |
|---|---|
| Fastener Length: | 3.160 Inches Minimum And 3.360 Inches Maximum |
| Head Style: | Flush Countersunk |
| Shank Diameter: | 0.248 Inches Minimum And 0.250 Inches Maximum |
| Shank Style: | Pin-rivet, Multiple Grooved |
| Head Major Diameter: | 0.344 Inches Minimum |
| Grip Length: | 0.876 Inches Minimum And 0.938 Inches Maximum |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/NAS1438-15 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.