

Description

Fastener Length: 2-7/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1438H04 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-01-390-6449 |
| Schedule B: | 7318.24.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



* See page 2 for technical characteristics

P/N NAS1438H04 Specifications

| | |
|---|---|
| Fastener Length: | 2.030 Inches Minimum And 2.230 Inches Maximum |
| Head Style: | Flush Countersunk |
| Shank Diameter: | 0.2480 Inches Minimum And 0.2495 Inches Maximum |
| Shank Style: | Pin-rivet, Multiple Grooved |
| Head Major Diameter: | 0.346 Inches Minimum And 0.399 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Grip Length: | 0.189 Inches Minimum And 0.250 Inches Maximum |
| Features Provided: | Sealant Vent Groove |
| Minimum Tensile Strength: | 2490 Pounds Per Square Inch |
| Shear Strength: | 9300 Double Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Astm A547 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1436 Thru 1442 Professional/industrial Association Standard |

How to Order

Order this swage locking pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1438H04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.