

Description

Swage Locking Pin part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1438H07 |
| Minimum Qty (MOQ): | 75 EA |
| NSN: | 5320-01-058-4116 |
| Schedule B: | 7318.24.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1438H07 Specifications

| | |
|---|---|
| Head Style: | Flush Countersunk |
| Shank Diameter: | 0.2480 Inches Minimum And 0.2495 Inches Maximum |
| Shank Style: | Pin-rivet, Multiple Grooved |
| Head Major Diameter: | 0.399 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Grip Length: | 0.376 Inches Minimum And 0.438 Inches Maximum |
| Features Provided: | Sealant Vent Groove |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 77.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall |
| Material Document And Classification: | Astm A547 Assn Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1438 Professional/industrial Association Standard |

How to Order

Order this swage locking pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1438H07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.