

## P/N NAS1446-06

### **Description**

Fastener Length: 2",

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS144606

Minimum Qty (MOQ): 20

NSN: 5320-00-558-3086

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1446-06 Specifications

Fastener Length:	1.880 Inches Minimum And 2.080 Inches Maximum
Head Style:	Err-090
Head Height:	0.056 Inches Minimum And 0.063 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.288 Inches Minimum And 0.302 Inches Maximum
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

## **How to Order**

Order this pin-rivet from our inventory online by visiting <a href="https://military-fasteners.com/pins/pin\_rivets/NAS1446-06">https://military-fasteners.com/pins/pin\_rivets/NAS1446-06</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.