

**Description**

Fastener Length: 2",

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS144606
Minimum Qty (MOQ):	20
NSN:	5320-00-558-3086
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1446-06 Specifications

<b>Fastener Length:</b>	1.880 Inches Minimum And 2.080 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.056 Inches Minimum And 0.063 Inches Maximum
<b>Shank Diameter:</b>	0.188 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.288 Inches Minimum And 0.302 Inches Maximum
<b>Grip Length:</b>	0.313 Inches Minimum And 0.375 Inches Maximum
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/NAS1446-06](https://military-fasteners.com/pins/pin_rivets/NAS1446-06) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.