

Description

Fastener Length: 2-5/16", locking pin,

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS144608
Minimum Qty (MOQ):	10
NSN:	5320-00-559-2910
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1446-08 Specifications

Fastener Length:	2.120 Inches Minimum And 2.320 Inches Maximum
Head Style:	Err-090
Head Height:	0.056 Inches Minimum And 0.063 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.288 Inches Minimum And 0.302 Inches Maximum
Grip Length:	0.439 Inches Minimum And 0.500 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this lock pin from our inventory online by visiting <https://military-fasteners.com/pins/lock+pins/NAS1446-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.