

Description

Fastener Length: 2-3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS144609
Minimum Qty (MOQ):	10
NSN:	5320-00-558-3084
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1446-09 Specifications

Fastener Length:	2.250 Inches Minimum And 2.450 Inches Maximum
Head Style:	Err-090
Head Height:	0.056 Inches Minimum And 0.063 Inches Maximum
Shank Diameter:	0.1880 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.288 Inches Minimum And 0.302 Inches Maximum
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Features Provided:	Casehardened
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	77.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Overall
Specification/standard Data:	80205-nas1446 Professional/industrial Association Standard

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/NAS1446-09 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.