

## P/N NAS1446-17

### **Description**

Fastener Length: 3-1/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS144617

Minimum Qty (MOQ): 5 EA

NSN: 5320-00-558-3135

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1446-17 Specifications**

Fastener Length:	3.120 Inches Minimum And 3.320 Inches Maximum
Head Style:	Err-090
Head Height:	0.056 Inches Minimum And 0.063 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.288 Inches Minimum And 0.302 Inches Maximum
Grip Length:	1.001 Inches Minimum And 1.062 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

## **How to Order**

Order this swage pin from our inventory online by visiting <a href="https://military-fasteners.com/rivets/pin\_rivets/NAS1446-17">https://military-fasteners.com/rivets/pin\_rivets/NAS1446-17</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.