

P/N NAS1446-18

Military-Fasteners.com

Description

Fastener Length: 3-1/4"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | NAS144618 |
|-------------------------|---|
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-00-558-3139 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N NAS1446-18 Specifications

| Fastener Length: | 3.120 Inches Minimum And 3.320 Inches Maximum |
|--|---|
| Head Style: | Err-090 |
| Head Height: | 0.056 Inches Minimum And 0.063 Inches Maximum |
| Shank Diameter: | 0.188 Inches Minimum And 0.190 Inches Maximum |
| Shank Style: | Pin-rivet, Multiple Grooved |
| Head Major Diameter: | 0.288 Inches Minimum And 0.302 Inches Maximum |
| Grip Length: | 1.063 Inches Minimum And 1.125 Inches Maximum |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this swage pin from our inventory online by visiting <u>https://military-fasteners.com/rivets/pin_rivets/NAS1446-18</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.