

Description

Fastener Length: 3-1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS144622
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-558-3134
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1446-22 Specifications

Fastener Length:	3.120 Inches Minimum And 3.320 Inches Maximum
Head Style:	Err-090
Head Height:	0.056 Inches Minimum And 0.063 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.288 Inches Minimum And 0.302 Inches Maximum
Grip Length:	1.313 Inches Minimum And 1.375 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this swage pin from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/NAS1446-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.