

Description

Fastener Length: 1-33/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1446H03
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-935-9066
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N NAS1446H03 Specifications

Fastener Length:	1.500 Inches Minimum And 1.520 Inches Maximum
Head Style:	Err-090
Head Height:	0.056 Inches Minimum And 0.063 Inches Maximum
Shank Diameter:	0.1880 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.288 Inches Minimum And 0.302 Inches Maximum
Grip Length:	0.126 Inches Minimum And 0.188 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Special Features:	Sealant Escape Groove
Material:	Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Astm A547 Assn Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1446 Professional/industrial Association Standard

How to Order

Order this swage pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1446H03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.