

Description

Fastener Length: 1-13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1446H04
Minimum Qty (MOQ):	20 EA
NSN:	5320-00-400-4064
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1446H04 Specifications

Fastener Length:	1.620 Inches Minimum And 1.820 Inches Maximum
Head Style:	Err-090
Head Height:	0.056 Inches Minimum And 0.063 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.288 Inches Minimum And 0.302 Inches Maximum
Grip Length:	0.189 Inches Minimum And 0.250 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Shear Strength:	95000 Single Pounds Per Square Inch
Heat Treatment:	As Fabricated Overall
Material:	Steel Overall
Material Document And Classification:	Ams 6300 Assn Std Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Stp 58-001,type 2,class 2,lockheed-georgia Co Mfr Ref Single Treatment Response Overall

How to Order

Order this swage pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1446H04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.