

Description

Swage Pin part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | NAS1446H05A |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-01-474-2290 |



P/N NAS1446H05A Specifications

| | |
|---|---|
| Head Style: | Err-090 |
| Head Height: | 0.056 Inches Minimum And 0.063 Inches Maximum |
| Shank Diameter: | 0.2010 Inches Minimum And 0.2025 Inches Maximum |
| Head Major Diameter: | 0.288 Inches Minimum And 0.302 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Grip Length: | 0.251 Inches Minimum And 0.312 Inches Maximum |
| Hardness Rating: | 77.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall |
| Special Features: | Sealant Escape Groove |
| Material: | Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall |
| Material Document And Classification: | Astm A547 Assn Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall |

How to Order

Order this swage pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1446H05A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.