

## Description

Fastener Length: 11/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1446H08
Minimum Qty (MOQ):	15 EA
NSN:	5320-00-009-3998
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1446H08 Specifications

<b>Fastener Length:</b>	0.689 Inches Minimum And 0.699 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.056 Inches Minimum And 0.063 Inches Maximum
<b>Shank Diameter:</b>	0.1880 Inches Minimum And 0.1895 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.288 Inches Minimum And 0.302 Inches Maximum
<b>Grip Length:</b>	0.439 Inches Minimum And 0.500 Inches Maximum
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Special Features:</b>	Sealant Escape Groove Type
<b>Material:</b>	Steel Comp 4037 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	66 Fed Std 1st Material Response Overall Or Aisi Assn Std All Material Responses Overall Or Sae Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this swage pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1446H08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.