

Description

Fastener Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1446H08
Minimum Qty (MOQ):	15 EA
NSN:	5320-00-009-3998
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N NAS1446H08 Specifications

Fastener Length:	0.689 Inches Minimum And 0.699 Inches Maximum
Head Style:	Err-090
Head Height:	0.056 Inches Minimum And 0.063 Inches Maximum
Shank Diameter:	0.1880 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.288 Inches Minimum And 0.302 Inches Maximum
Grip Length:	0.439 Inches Minimum And 0.500 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Shear Strength:	95000 Single Pounds Per Square Inch
Special Features:	Sealant Escape Groove Type
Material:	Steel Comp 4037 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	66 Fed Std 1st Material Response Overall Or Aisi Assn Std All Material Responses Overall Or Sae Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this swage pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1446H08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.