

Description

Fastener Length: 3-7/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1448N12
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-492-3531
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1448N12 Specifications

<b>Fastener Length:</b>	3.030 Inches Minimum And 3.230 Inches Maximum
<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.074 Inches Minimum And 0.081 Inches Maximum
<b>Shank Diameter:</b>	0.2480 Inches Minimum And 0.2495 Inches Maximum
<b>Head Major Diameter:</b>	0.363 Inches Minimum And 0.377 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>End Item Identification:</b>	Ch-53 Helicopter
<b>Grip Length:</b>	0.740 Inches Minimum And 0.760 Inches Maximum
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	78.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
<b>Material:</b>	Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Astm A547 Assn Std All Material Responses Overall
<b>Surface Treatment:</b>	Nickel Overall And Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2416 Assn Std Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1448 Professional/industrial Association Standard

## How to Order

Order this swage pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1448N12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.