

Description

Fastener Length: 3-7/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1448N12
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-492-3531
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1448N12 Specifications

Fastener Length:	3.030 Inches Minimum And 3.230 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.074 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.2480 Inches Minimum And 0.2495 Inches Maximum
Head Major Diameter:	0.363 Inches Minimum And 0.377 Inches Maximum
Lubrication:	Cetyl Alcohol
End Item Identification:	Ch-53 Helicopter
Grip Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	78.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Astm A547 Assn Std All Material Responses Overall
Surface Treatment:	Nickel Overall And Cadmium Overall
Surface Treatment Document And Classification:	Ams 2416 Assn Std Single Treatment Response Overall
Specification/standard Data:	80205-nas1448 Professional/industrial Association Standard

How to Order

Order this swage pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1448N12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.