

Description

Fastener Length: 63/64", Thread: 1/4-28, Head Width: 7/32", Thread Length: 33/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS144A16
Minimum Qty (MOQ):	1
NSN:	5306-00-807-9280
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS144A16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.475 Inches Minimum And 0.525 Inches Maximum
Fastener Length:	0.985 Inches Minimum And 1.015 Inches Maximum
Head Style:	Bevel-conical
Head Diameter:	0.430 Inches Minimum And 0.438 Inches Maximum
Head Height:	0.226 Inches Nominal
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.081 Inches Maximum First Hole
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.219 Inches Minimum And 0.221 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.834 Inches Minimum First Hole And 0.854 Inches Maximum First Hole
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 3140 Overall Or Steel Comp 3135 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas144 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS144A16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.