

Description

Fastener Length: 0-63/64", Hole Diameter: 1/32", Thread: 1/4-28, Head Width: 7/32", Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS144ADH16
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-250-5584
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS144ADH16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.485 Inches Minimum And 0.515 Inches Maximum
Fastener Length:	0.985 Inches Minimum And 1.015 Inches Maximum
Head Diameter:	0.430 Inches Minimum And 0.438 Inches Maximum
Head Height:	0.226 Inches Nominal
Hole Diameter:	0.046 Inches Nominal
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.081 Inches Maximum First Hole
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.219 Inches Minimum And 0.221 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Round Internal Hexagon
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.844 Inches Nominal First Hole
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 3140 Overall Or Steel Comp 3135 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas144 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS144ADH16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.